



# TIGER CAT

**Compact size.  
Full-size performance.**

## **Specifications**

### **Engine Options:**

- 22hp Kawasaki FS, air-cooled, twin cylinder, vertical shaft
- 22hp Kawasaki FX, air-cooled, twin cylinder, vertical shaft
- 23hp Kohler Command Pro, air-cooled, twin cylinder, vertical shaft
- 23hp Kawasaki FX, air-cooled, twin cylinder, vertical shaft
- 25hp Kohler Command Pro, air-cooled, twin cylinder, vertical shaft, Electronic Fuel Injection (EFI)
- 26hp Kohler Command Pro, air-cooled, twin cylinder, vertical shaft, Electronic Fuel Injection (EFI)
- 27hp Briggs & Stratton Com. Turf Series, air-cooled, twin cylinder, vert. shaft

### **Fuel Capacity/Design:**

7 gallons, dual fuel tanks with molded-in cupholder

### **Travel Control:**

Twin steering controls with gas dampers for smooth, precise maneuverability.

### **Ground Speed:**

Up to 10mph forward, 4.5mph reverse

### **Main Frame Construction:**

Steel tube frame, full-length, fully-welded

### **Drive Tires:**

- 24 x 9.5 -12, 4 ply (48" & 52" models)
- 24 x 12 - 12, 4 ply (61" models)

### **Caster Tires:**

- 13 x 5 - 6, 4 ply, pneumatic (48" & 52" models)
- 13 x 6.5 - 6, 4 ply, pneumatic (61" models)

### **Caster Wheel Bearings:**

Tapered roller bearings

### **Front Caster Arm Design:**

Bolt-on for easy replacement if necessary

### **Hydraulic Pumps:**

Dual Pumps; 10cc displacement, Hydro-Gear

### **Hydraulic Oil Cooler:**

Not required - Large capacity cooling reservoir

**WWW.SCAG.COM**

(Continued)



<b>Belts:</b>	Kevlar cord. Self-adjusting, spring-loaded, self-tightening
<b>Drive/Load Pulleys:</b>	Split-steel design -- stronger and lighter weight than cast-iron
<b>Instrument Panel :</b>	Key switch, throttle, manual choke, BBC switch
<b>Seat:</b>	Suspension seat, adjustable with padded arm rests on most models. Some models feature a "Soft-Ride" seat.
<b>PTO - Electric Clutch:</b>	Ogura GT3.5 - 250 ft lb / adjustable air-gap
<b>Cutter Decks:</b>	48", 52", & 61" Velocity Plus Decks. Floating, adjustable, anti-scalping design.
<b>Cutter Deck Construction:</b>	Tri-Plate, welded: 48" with 7 gauge deck top and skirt, 10 gauge & 11 gauge reinforcement plates; 52" with 10 gauge top, 7 gauge skirt, 10 gauge & 11 gauge reinforcement plates; 61" with 10 gauge top, 7 gauge skirt, 7 gauge & 11 gauge reinforcement plates.
<b>Cutter Deck Drive:</b>	Belt driven -- Straight belt for long life, not a twisted "mule" drive
<b>Number of Anti-Scalp Wheels:</b>	<ul style="list-style-type: none"> <li>• 48": 4 wheels in 4 positions</li> <li>• 52": 4 wheels in 4 positions</li> <li>• 61": 7 wheels in 5 positions</li> </ul>
<b>Cutter Deck Spindles:</b>	Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty
<b>Cutter Deck Height Adjustment:</b>	Foot pedal lift with self-locking mechanism at transport position
<b>Cutting Range:</b>	1" to 5" in .25" increments
<b>Number of Cutter Blades:</b>	3 Marbain blades
<b>Total Length:</b>	<ul style="list-style-type: none"> <li>• 48" and 52" models: 80"</li> <li>• 61" models: 83"</li> </ul>
<b>Total Width (with discharge chute in mowing position):</b>	<ul style="list-style-type: none"> <li>• 48" models: 60.5"</li> <li>• 52" models: 64.5"</li> <li>• 61" models: 73.5"</li> </ul>
<b>Total Width (with discharge chute in transport position):</b>	<ul style="list-style-type: none"> <li>• 48" models: 49"</li> <li>• 52" models: 53"</li> <li>• 61" models: 62"</li> </ul>
<b>Height (with ROPS):</b>	66"
<b>Height (with ROPS folded*):</b>	54"
<b>Weight (with ROPS):</b>	<ul style="list-style-type: none"> <li>• 48" models: 1030-1050 lbs.</li> <li>• 52" models: 1100 lbs.</li> <li>• 61" models: 1150 lbs.</li> </ul>
<b>Warranty:</b>	<ul style="list-style-type: none"> <li>• 2 Yr. Commercial Mower Warranty—Parts &amp; labor.</li> <li>• 3 Yr. / 500 Hour Non-Commercial Mower Warranty—Parts &amp; labor.</li> <li>• 3 Yr. Deck Warranty—First &amp; second years parts &amp; labor; third year parts.</li> <li>• 3 Yr. Spindle Warranty—First &amp; second years parts &amp; labor; third year parts.</li> <li>• 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.</li> </ul>



All specifications subject to change without notice. Actual ground speeds may vary.

**WWW.SCAG.COM**