

Skid-Steer Loaders / S62 Skid-Steer Loader

S62 Loader Specifications & Options

Review the complete list of S62 skid-steer loader specs and compare them with other Bobcat models.

■ Standard
 Optional
N/A Not Applicable

Units **US**

Bobcat S62 T4

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	68 hp
Turbocharged Engine	<input checked="" type="checkbox"/>

Performance

Rated Operating Capacity (ISO)	2,100 lb
Tipping Load	4200 lb
Operating Weight	6884 lb
Travel Speed	7.4 mph
Travel Speed (2-speed option)	11 mph

Capacities

Fuel Tank	28.3 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	17.6 gal/min
Auxiliary High Flow	26.9 gal/min

Dimension

Length	135 in
Length without Attachment	107 in
Length with Standard Bucket	135 in
Width	64.6 in
Width (with bucket)	68 in
Height	80.5 in
Height with Operator Cab	80.5 in
Height to Bucket Hinge Pin	114.5 in
Reach @ Maximum Height	20.4 in
Turning Radius	79.8 in
Wheelbase	44.6 in

Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Adjustable Seat	<input type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>
Sound Option	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Parking Brake	<input type="checkbox"/>
Radio	<input checked="" type="checkbox"/>
Rear Window	<input type="checkbox"/>
Top Window	<input type="checkbox"/>
Lift-Arm Support	<input type="checkbox"/>
Seat Belt	Standard 2-Point Lap Belt and Optional 3-Point Shoulder Belt on Two-Speed Models.
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Spark Arrestor Muffler	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	<input checked="" type="checkbox"/>
Ride Control	<input checked="" type="checkbox"/>
Rear Hydraulics	<input checked="" type="checkbox"/>

Horn	
	

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.